

Tampa

Tuft gauge	1/10 COC		ISO 2424
Pilecomposition	100% PA SDN		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	AB		ISO 2424
Width	400 cm	± 1%	EN 984
Pile Weight	1100 gr/m ²		ISO 8543
Total weight	AB : 2000 gr/m ²	± 15%	ISO 8543
Pile height	7 mm	± 2 mm	ISO 1766
Total Height	AB : 9 mm		ISO 1765
Number of knots	199475 /m ²	-7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1		EN 13501-1
Transversal resistance	Ω		ISO 10965
Use Area	Heavy project use (33)		EN 1307
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Luxury class	LC3		EN 1307
Pictures	www.condorcontract.com		

Floorsymbols



Certificates

CE

2023

Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307

DOP: C-022AT244

Reaction to fire:
 Cfl-s1
 1658

Slip resistance: DS
 AB

Resilient floor
 covering to be
 used within a
 building

