

## Java

<b>Tuft gauge</b>	5/32 cut pile		ISO 2424
<b>Pilecomposition</b>	100% PES		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	AB, Felt		ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1%	EN 984
<b>Pile Weight</b>	1100 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	AB : 2000 gr/m <sup>2</sup> Felt : 2100 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	12 mm	± 2 mm	ISO 1766
<b>Total Height</b>	AB : 14 mm Felt : 15 mm		ISO 1765
<b>Number of knots</b>	73080 /m <sup>2</sup>	-7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1		EN 13501-1
<b>Use Area</b>	Medium domestic use (22)		EN 1307
<b>GUT Nr.</b>	2911D8AB		www.pro-dis.info
<b>Thermal resistance</b>	ca. 0.06 (0.6 TOG) M <sup>2</sup> KW		ISO 8302
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01

## Floorsymbols



## Certificates

**CE**  
2021  
Condor Carpets  
Euroweg 3  
8061 SB Hasselt  
EN1307  
DOP: C-025A.J055  
Reaction to fire:  
Cfl-s1  
1658  
Slip resistance: DS  
AB  
Resilient floor  
covering to be  
used within a  
building

**CE**  
2021  
Condor Carpets  
Euroweg 3  
8061 SB Hasselt  
EN1307  
DOP: C-025F.J055  
Reaction to fire:  
Cfl-s1  
1658  
Slip resistance: DS  
Felt  
Resilient floor  
covering to be  
used within a  
building





