





















Technický list

Xtreme

Informace o výrobku	EN ISO 10582			
Oblast použití / zátěž	EN ISO 10874 EN 685			34 - 43
Celková tloušťka	EN ISO 24346 EN 428			2,00 mm
Výška nášlapné vrstvy	EN ISO 24340 EN 429			0,70 mm
Celková hmotnost	EN ISO 23997 EN 430			2800 g/m ²
Šíře role	EN ISO 24341 EN 426			2 • 3 • 4 m

Technické informace

Rozměrová stálost	EN ISO 23999 EN 434			≤ 0,40 %
Stálobarevnost	EN ISO 105 B02			≥ 6 stupňů
Zbytkový otlak	EN ISO 24343-1 EN 433			0,1 mm
Hořlavost	EN 13501-1			Bfl-S1
Protiskluznost	DIN 51130			R10
Dynamický koeficient tření	EN 13893			> 0,6
Odolnost proti otěru	EN 660-2			T
Kročejový útlum hluku	EN ISO 717/2			Δ Lw 6 dB
Podlahové vytápění	EN 12667			vhodný
Statický elektrický náboj	EN 1815			< 2kV
Tepelný odpor	ISO 8302			0,014 m ² /Kw
Tepelný vodivost	EN 12524			0,14 W/(m.K)
Chemická odolnost	EN 423 ISO 26987			odolný
Kolečková židle	EN ISO 4918 EN 12529			vhodné (typ H)
Antibacterial test	EN ISO 846			ano

Powerful Bacterial Protection Built-in

Our vinyl floors have bacteriostatic properties built-in and undergo severe testing to achieve ISO 846 standards. This demonstrates our dedication to give our customers total peace of mind.



The Environment

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



100% Phthalate Free
For all products produced from May 2017 onwards



100% Recyclable



UPEC-A+



This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.



E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)



Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)