


















Technický list

Centaur

Informace o výrobku	EN ISO 26986			
Oblast použití / zátěž	ISO 10874 (EN 685)		23 - 33 - 42	
Celková tloušťka	EN ISO 24346 (EN 428)		2,25	mm
Výška nášlapné vrstvy	EN ISO 24340 (EN 429)		0,60	mm
Odolnost proti opotřebení	EN 660-2		T	
Celková hmotnost	EN ISO 23997 (EN 430)		2330	g/m ²
Šíře role	EN ISO 24341 (EN 426)		2 • 3 • 4	m
Technické informace				
Hořlavost	EN 13501-1		Bfl/S1	
Protiskluznost	DIN 51130		R10	
Dynamický koeficient tření	EN 13893		> 0,6	
Kročejový útlum hluku	EN ISO 717/2		Δ Lw 10	dB
Zbytkový otlak	EN ISO 24343-2 (EN 433)		0,2	mm
Rozměrová stálost	EN ISO 23999 (EN 434)		≤ 0,40	%
Stálost barev	EN ISO 105 B02		≥ 6	úroveň
Podlahové vytápění	EN 12667		vhodný	
Tepelný odpor	ISO 8302		0,014	m ² /Kw
Tepelná vodivost	EN 12524		0,16	W/(m.K)
Sklon ke vzniku statické elektřiny	EN 1815		< 2kV	
Kolečková židle	EN ISO 4918		vhodné (typ H)	
Chemická odolnost	ISO 26987 (EN 423)		odolný	
Antibacterial test	ISO 846		ano	

Antibacterial test Powerful Bacterial Protection Built-in

Our vinyl floors have bacteriostatic properties built-in and undergo severe testing to achieve ISO 846 standards. This demonstrates our dedication to give our customers total peace of mind.



The Environment

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



100% Phthalate Free
For all products produced
from May 2017 onwards



100% Recyclable



This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.



E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m³ of air)



Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)