

KESWICK

Manufacturing process	Tufted	ISO 2424
Gauge	5/32" Loop	
Pilecomposition	100% PP	ISO 2424
Primary backing	Woven PP	ISO 2424
Secondary backing	Starback + Felt	ISO 2424
Width	400 cm ± 1%	EN 986
Pile weight	approx. 650 gr/m ²	ISO 8543
Total weight	Starback : approx. 1682 gr/m ² Felt : approx. 1720 gr/m ² ± 15%	ISO 8543
Pile height	approx. 4,5 mm	ISO 1765
Total height	Starback : approx. 6,6 mm + 15% / -10% Felt : approx. 7.8 mm	ISO 1765
Number of knots	approx. 121.320 /m ² + 10% / -7,5%	ISO 1763
Fire classification	Starback : Efl (EN13501-1) Felt : Efl (EN13501-1)	EN 13501-1
Light fastness	≥ 5	105-B02
Wearability	≥ 4,5	105-X12
Water fastness	≥ 4,5	105-E01
Thermal resistance	0,130 m ² K/W	ISO 8302
Sound isolation	0,10 dB	ISO 10140
GUT Nr.	Starback : 4C65FFB2 Felt : 0649E850	

Floorsymbols Starback



Floorsymbols Felt



Certificates

