

## RUBIN

<b>Manufacturing process</b>	Tufted	ISO 2424
<b>Gauge</b>	1/10" Loop	
<b>Pilecomposition</b>	100% PP	ISO 2424
<b>Primary backing</b>	Woven PP	ISO 2424
<b>Secondary backing</b>	AB + Gel + Felt	ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1% EN 986
<b>Pile weight</b>	approx. 540 gr/m <sup>2</sup>	ISO 8543
<b>Total weight</b>	AB : approx. 1782 gr/m <sup>2</sup> Gel : approx. 1560 gr/m <sup>2</sup> Felt : approx. 1732 gr/m <sup>2</sup>	± 15% ISO 8543
<b>Pile height</b>	approx. 2,1 mm	ISO 1765
<b>Total height</b>	AB : approx. 5,6 mm Gel : approx. 5,0 mm Felt : approx. 6,0 mm	+ 15% / -10% ISO 1765
<b>Number of knots</b>	approx. 213.165 /m <sup>2</sup>	+ 10% / -7,5% ISO 1763
<b>Fire classification</b>	AB : Cfl-S1 verlijmd Gel : Efl Felt : Efl	EN 13501-1
<b>Light fastness</b>	≥ 5	105-B02
<b>Wearability</b>	≥ 4	105-X12
<b>Water fastness</b>	≥ 4	105-E01
<b>Thermal resistance</b>	0,120 m <sup>2</sup> K/W	ISO 8302
<b>Sound insulation</b>	10,0 dB	ISO 10140
<b>GUT Nr.</b>	AB : A7F2B09E Gel : 12D24D4E Felt : E914E3D4	
<b>Characteristics</b>	Gel = 400 cm. wide only	

### Floorsymbols AB



### Floorsymbols Felt



### Floorsymbols Gel



### Certificates

<p>EN 14041 17</p> <p><b>CE</b></p> <p>Reaction to fire: Cfl-S1 verlijmd</p> <p>Slip resistance: DS AB DOP: 1058-124338</p> <p>Textile Floorcovering EN1307</p>	<p>EN 14041 17</p> <p><b>CE</b></p> <p>Reaction to fire: Efl</p> <p>Slip resistance: DS Felt DOP: 1058-124337</p> <p>Textile Floorcovering EN1307</p>	<p>EN 14041 16</p> <p><b>CE</b></p> <p>Reaction to fire: Efl</p> <p>Slip resistance: DS Gel DOP: 1058-124115</p> <p>Textile Floorcovering EN1307</p>
---	---	--

