

## BONANZA

|                              |                                                                                    |            |
|------------------------------|------------------------------------------------------------------------------------|------------|
| <b>Manufacturing process</b> | Tufted                                                                             | ISO 2424   |
| <b>Gauge</b>                 | 5/32" Loop                                                                         |            |
| <b>Pilecomposition</b>       | 100% PP                                                                            | ISO 2424   |
| <b>Primary backing</b>       | Woven PP                                                                           | ISO 2424   |
| <b>Secondary backing</b>     | AB + Felt                                                                          | ISO 2424   |
| <b>Width</b>                 | 400 cm, 500 cm ± 1%                                                                | EN 986     |
| <b>Pile weight</b>           | approx. 360 gr/m <sup>2</sup>                                                      | ISO 8543   |
| <b>Total weight</b>          | AB : approx. 1496 gr/m <sup>2</sup> ± 15%<br>Felt : approx. 1498 gr/m <sup>2</sup> | ISO 8543   |
| <b>Pile height</b>           | approx. 3,5 mm                                                                     | ISO 1765   |
| <b>Total height</b>          | AB : approx. 5,3 mm + 15% / -10%<br>Felt : approx. 6,0 mm                          | ISO 1765   |
| <b>Number of knots</b>       | approx. 106.155 /m <sup>2</sup> + 10% / -7,5%                                      | ISO 1763   |
| <b>Fire classification</b>   | AB : Efl<br>Felt : Efl                                                             | EN 13501-1 |
| <b>Light fastness</b>        | ≥ 5                                                                                | 105-B02    |
| <b>Wearability</b>           | ≥ 4                                                                                | 105-X12    |
| <b>Water fastness</b>        | ≥ 4                                                                                | 105-E01    |
| <b>Thermal resistance</b>    | 0,120 m <sup>2</sup> K/W                                                           | ISO 8302   |
| <b>Sound isolation</b>       | 0,10 dB                                                                            | ISO 10140  |
| <b>GUT Nr.</b>               | Felt : 95BAF8E6                                                                    |            |

## Floorsymbols Felt



## Certificates

