

## FLAMINGO

|                              |                                                                              |                           |
|------------------------------|------------------------------------------------------------------------------|---------------------------|
| <b>Manufacturing process</b> | Tufted                                                                       | ISO 2424                  |
| <b>Gauge</b>                 | 5/32" Loop                                                                   |                           |
| <b>Pilecomposition</b>       | 100% PP                                                                      | ISO 2424                  |
| <b>Primary backing</b>       | Woven PP                                                                     | ISO 2424                  |
| <b>Secondary backing</b>     | AB + Felt                                                                    | ISO 2424                  |
| <b>Width</b>                 | 400 cm, 500 cm                                                               | ± 1%<br>EN 986            |
| <b>Pile weight</b>           | approx. 600 gr/m <sup>2</sup>                                                | ISO 8543                  |
| <b>Total weight</b>          | AB : approx. 1718 gr/m <sup>2</sup><br>Felt : approx. 1760 gr/m <sup>2</sup> | ± 15%<br>ISO 8543         |
| <b>Pile height</b>           | approx. 5,0 mm                                                               | ISO 1765                  |
| <b>Total height</b>          | AB : approx. 6,0 mm<br>Felt : approx. 7,0 mm                                 | + 15% / -10%<br>ISO 1765  |
| <b>Number of knots</b>       | approx. 75.825 /m <sup>2</sup>                                               | + 10% / -7,5%<br>ISO 1763 |
| <b>Fire classification</b>   | AB : Efl<br>Felt : Efl                                                       | EN 13501-1                |
| <b>Light fastness</b>        | ≥ 5                                                                          | 105-B02                   |
| <b>Wearability</b>           | ≥ 4                                                                          | 105-X12                   |
| <b>Water fastness</b>        | ≥ 4                                                                          | 105-E01                   |
| <b>Thermal resistance</b>    | 0,130 m <sup>2</sup> K/W                                                     | ISO 8302                  |
| <b>Sound insulation</b>      | 20,0 dB                                                                      | ISO 10140                 |
| <b>GUT Nr.</b>               | AB : DBDCFE7<br>Felt : 7F62A7A7                                              |                           |

## Floorsymbols



## Certificates

