

## LA MANGA

<b>Manufacturing process</b>	Tufted	ISO 2424
<b>Gauge</b>	5/32" Loop	
<b>Pilecomposition</b>	100% PP	ISO 2424
<b>Primary backing</b>	Woven PP	ISO 2424
<b>Secondary backing</b>	AB + Felt	ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1% EN 986
<b>Pile weight</b>	approx. 370 gr/m <sup>2</sup>	ISO 8543
<b>Total weight</b>	AB : approx. 1403 gr/m <sup>2</sup> Felt : approx. 1425 gr/m <sup>2</sup>	± 15% ISO 8543
<b>Pile height</b>	approx. 4,0 mm	ISO 1765
<b>Total height</b>	AB : approx. 6,0 mm Felt : approx. 6,5 mm	+ 15% / -10% ISO 1765
<b>Number of knots</b>	approx. 93.500 /m <sup>2</sup>	+ 10% / -7,5% ISO 1763
<b>Fire classification</b>	AB : Cfl-S1 verlijmd Felt : Cfl-S1 verlijmd	EN 13501-1
<b>Light fastness</b>	≥ 5	105-B02
<b>Wearability</b>	≥ 4	105-X12
<b>Water fastness</b>	≥ 4	105-E01
<b>Thermal resistance</b>	0,120 m <sup>2</sup> K/W	ISO 8302
<b>Sound isulation</b>	10,0 dB	ISO 10140
<b>GUT Nr.</b>	AB : 89ECF791 Felt : 25FD25DE	

### Floorsymbols AB



### Floorsymbols Felt



### Certificates

