

TITAN

Manufacturing process	Tufted	ISO 2424
Gauge	5/32" Loop	
Pilecomposition	100% PP	ISO 2424
Primary backing	Woven PP	ISO 2424
Secondary backing	AB + Felt	ISO 2424
Width	400 cm, 500 cm	± 1% EN 986
Pile weight	approx. 380 gr/m ²	ISO 8543
Total weight	AB : approx. 1383 gr/m ² Felt : approx. 1360 gr/m ²	± 15% ISO 8543
Pile height	approx. 3,5 mm	ISO 1765
Total height	AB : approx. 6,0 mm Felt : approx. 6,5 mm	+ 15% / -10% ISO 1765
Number of knots	approx. 120.960 /m ²	+ 10% / -7,5% ISO 1763
Fire classification	AB : Efl (EN13501-1) Felt : Efl (EN13501-1)	EN 13501-1
Light fastness	≥ 5	105-B02
Wearability	≥ 4,5	105-X12
Water fastness	≥ 4,5	105-E01
Thermal resistance	0,120 m ² K/W	ISO 8302
Sound isulation	10,0 dB	ISO 10140
GUT Nr.	AB : 6F1EF980 Felt : AAFD71A0	

Floorsymbols AB



Floorsymbols Felt



Certificates

